

NATURAL CURRENT SPECIFICATIONS

TECHNICAL SPECIFICATIONS

Everything Else You Need to Know



Body

- Size: 35" W x 35.5" L x 12" H
- Weight: 38 lbs.
- Body Type: Cross-link plastic

Pump

- Flow Rate: 18 Gallons-Per-Minute (GPM)
- Flow Rate: 1,100 Gallons-Per-Hour (GPH)
- Maximum Head: 10 ft
- Hose Outlet: 1 1/8"
- Maximum water Temperature: 104°F
- Typical Life: 1500 to 2500 hours
- New Replacement Cost: \$39.00
- Power: 12V, 2.9A
- Shaft Material: Stainless Steel
- Certifications: UL, CE and ISO 8849

Filter

- Media: 175 pleat count, 3 oz. Reemay 2033; 20 Micron Cartridges
 - Effective Filtration Area: 96 sq ft
-

Solar Panel

- Solar 60W, 12V, 3.3A, Polycrystalline Silicon
 - Operating temperature: -40°C to + 85°C / -40°F to +185°F
 - Dimensions: 25.7" x 25.2" x 1.38" / 652 mm x 639 mm x 35 mm
 - Weight: 13.21 lbs. / 6 kg
 - Front glass: 3.2 mm tempered
 - Max Load: 5.4 kPa
 - Certifications: UL, TUV, IEC, and ETL
-

Shipping

- Box Size: 35" W x 35.5" L x 12.75" H
- Weight: 41 lbs.



NATURAL CURRENT | PO Box 3803, Dana Point, CA 92629 | Phone: 1-855-372-8467
E-Mail: info@naturalcurrent.com | Web Site: <http://www.naturalcurrent.com>