

®

TropiCal





An economy heat pump designed to fit any budget

- Optimum heat output in small footprint
- Large surface and corrosion resistant evaporator
- Vinyl coated fan grill
- Microprocessor controlled automatic defrost allows operation down to the mid to lower 40s
- High performance titanium heat exchanger (Patented ThermoLink heat exchanger in T115 model)



#10663 10_11 v1

	50 Hz			60 Hz		
	T35	T55	T75	T55	T75	T115
Efficiency						
KW Output	10.26	12.02	16.85	14.65	20.52	32.83
BTU Output	35,000	41,000	57,500	50,000	70,000	112,000
Coefficient of Performance	6.5	6.6	6.0	5.8	5.7	5.7
KW Input	1.5	1.8	2.8	2.5	3.7	5.8
Electrical						
Voltage/Hz/Phase	200-240/50/1	380-420/50/3 200-240/50/1	380-420/50/3 200-240/50/1	208-230/60/1	208-230/60/1	208-230/60/1
Maximum Fuse Size	20	3 ph - 10 1 ph - 25	3 ph - 15 1 ph - 30	30	45	60
Minimum Circuit Ampacity	12.2	3 ph - 6.9 1 ph - 15.6	3 ph - 9.1 1 ph - 19.5	19.7	25.8	40
Refrigerant	R410A	R410A	R410A	R410A	R410A	R410A
Heat Exchanger	Tube in Tube	Tube in Tube	Tube in Tube	Tube in Tube	Tube in Tube	ThermoLink
Water Flow						
Min./Max. water flow (m3h)	4.5/10.2	4.5/10.2	4.5/10.2	4.5/10.2	4.5/10.2	6.8/15.9
Min./Max. water flow (gpm)	20/45	20/45	20/45	20/45	20/45	30/70
Physical						
Shipping Weight (kg)	109	109	125	109	125	141
Shipping Weight (lbs)	240	240	275	240	275	310
Size						
Length x Width x Height (cm)	92 x 61 x 69	92 x 61 x 69	92 x 61 x 79	92 x 61 x 69	92 x 61 x 79	94 x 72 x 94
Length x Width x Height (in)	36" x 24" x 27"	36" x 24" x 27"	36" x 24" x 31"	36" x 24" x 27"	36" x 24" x 31"	37" x 28" x 37"



2737 24th Street North • St. Petersburg, FL 33713 • 727.823.5642 • aquacal.com

