



AT75

POOL/SPA HEAT PUMP

PC Logic Controls

- reliable advanced digital microprocessor
- digital temperature settings for superior accuracy
- self diagnostic readouts eliminate needless service calls
- dual thermostat for pool and spa settings
- interfaces with all computerized pool/spa controls
- smart defrost control allows unit to operate to lowest possible temperatures

Scroll Compressor

- high efficiency, quiet operation
- superior design compared to piston compressors for years of trouble free operation

Ultraviolet Protected ABS Plastic Cabinet

- will not rust, corrode or crack
- **Tube in Tube Titanium Heat Exchanger**
- impervious to pool chemicals and low pH

**2 YEAR LABOR WARRANTY
7 YEAR PARTS WARRANTY
15 YEAR TITANIUM TUBE
HEAT EXCHANGER WARRANTY**

BTUs

80/80/80	70,000*
80/80/63	67,000**
80/50/63	46,000**

Coefficient of Performance

80/80/80	5.5
80/80/63	5.3
80/50/63	4.0

Refrigerant R410A**Heat Exchanger** Titanium**Electrical**

KW Input..... 3.7

Voltage/Hz/Phase..... 208-230/60/1

Minimum Circuit Ampacity..... 25.8

Maximum Fuse Size..... 45

Water Flow

Minimum/Maximum (gpm)..... 20/45

PhysicalWeight (lbs) 265 |

Shipping..... 275

Size..... L 36" x W 24" x H 31"

Compact Design



AQUATHERM HEAT PUMPS

2213 ANDREA LANE • FORT MYERS, FL 33912

239/482-0606 • FAX 239/482-7737

WWW.AQUATHERMHEATPUMPS.COM

* Ratings outside the scope of the ARI standard 1160 water temp/ambient air/relative humidity ** Rated in accordance with ARI standard 1160 water temp/ambient air/relative humidity