



# FRONIUS IG

## GRID-TIED INVERTERS FOR PHOTOVOLTAIC SYSTEMS

- Light Weight** At 42 lbs, the FRONIUS IG inverters are the lightest grid-connected inverters making them easy-to-install.
- More Energy** MIX™ Concept allows your system to output more energy under part-load conditions.
- Lower Cost** Integrated DC / AC breakers reduce installation time and complexity.
- LCD Display** Comes standard with every FRONIUS IG and tracks more than 20 critical system performance parameters.
- Powerful** At 4000, 4500 and 5100 Watts, these inverters deliver more power output for higher performance installations.
- Reliable** Fronius has been in business for over 50 years and has more than 100,000 inverters installed worldwide.



POWERING YOUR FUTURE

# FRONIUS IG

## FRONIUS IG 4000 / 5100 / 4500-LV - Specifications

Input data	IG 4000	IG 5100	IG 4500-LV
Recommended PV power (Wp)	3000 – 5400	4000 – 6300	3600 – 5500
Operating DC voltage range (V)	150 – 450	150 – 450	150 – 450
Max. DC input voltage (V)	500	500	500
Nominal input voltage (V)	270	270	270
Max. DC input current (A)	26.1	33.2	29.3
Output data	IG 4000	IG 5100	IG 4500-LV
Nominal output power (W)	4000	5100	4500
Maximum output power (W) @ (40°C)	4000	5100	4500
Nominal AC output voltage (V)	240		208
Operating AC voltage range (V)	212 – 264 (240 +10% / -12%)		183 – 227 V
Nominal AC current (A)	16.7	21.3	21.6
Maximum AC current (A)	16.7	21.3	21.6
Maximum utility back feed current (A)	0.0	0.0	0.0
Max. continuous output fault current (A)	35.2	35.2	35.2
Nominal output frequency (Hz)	60		
Operating frequency range Hz	59.3 – 60.5 (60+ 0.5 / - 0.7)		
Total harmonic distortion (%)	< 5		
Power Factor (cos phi)	1		
General data	IG 4000	IG 5100	IG 4500-LV
Max. efficiency (%)	94.4	94.4	94.4
Consumption in stand-by (night) (W)	< 0.15		
Consumption during operation (W)	15		
Protection Type	NEMA 3R		
Cooling	Controlled forced ventilation		
Size l x w x h	28.34x 16.46 x 8.78 in (720 x 418 x 223 mm)		
Weight	41.8 lb. (19 kg)		
Ambient temperature range	5 to 122 °F (-15 ... 50 °C)		
Integrated DC and AC disconnects	standard		
Protections			
Ground fault protection	Internal GFDI, in accordance with UL 1741 and NEC		
DC reverse polarity protection	Internal diode		
Islanding protection	Internal, in accordance with UL 1741 and NEC		
Over temperature	Output power derating		
Surge Protection	Internal DC & AC protection, Tested to 6 kV		
Compliance			
Safety	UL 1741		
EMI	FCC Part 15; Class B		
Anti-Islanding protection	UL 1741, IEEE 929		
Ground fault detector and interrupter	Compliant with NEC Art. 690 requirements, UL 1741		
Miscellaneous			
Maximum AC over current protection	Two-pole, 30 A circuit breaker		
AC wire sizing	Use maximum AWG 6 194°F (90 °C) copper wire		
DC wire sizing	Use maximum AWG 8 194°F (90 °C) copper wire		
AC disconnect	32 A		
DC disconnect	30 A		
Warranty	5 Years; 10 Years available		

Distributed by



**Fronius USA LLC**  
**Solar Electronic Division**  
 5266 Hollister Ave., #117  
 Santa Barbara, California 93111  
 E-Mail: pv-us@fronius.com  
[www.fronius.com](http://www.fronius.com)