

F-Series 90W PV Module SPM090P-TS-F

Solartech F-Series Modules

Solartech photovoltaic F-Series Modules are constructed with high efficient polycrystalline solar cells and produce higher output per module than others in it class. This industrial grade module is an industry standard among various industry professionals.

Features

- Accessible junction box with 4-1/2 knockout for ease of installation.
- (EVA) with TPT cushions the solar cells within the laminate an ensures the operating characteristics of the solar cells under virtually any climatic condition
- •Rigid anodized aluminum frame and low iron tempered glass
- · Easily accessible grounding points on all four corners for fast installation
- Proven junction box technology



Reliability

- Proven superior field performance
- Tight power tolerance

Qualifications and Certifications










UL No.: E330673 TUV No.:0000022551 IEC No.:C1-ASN07001 ETL No.:4001057

Applications

- Traffic & Safety
- Federal Government
- Oil & Gas
- Security
- Telecommunications
- Water and Wastewater
- Weather & Environmental Monitoring
- RV Camper
- Emergency Power
- Telemetry
- SCADA, RTU, GPS
- Marine
- Area Lighting & Sign

90W
18.3V
5.04A
5.38A
22.2V
13.27%
±5%
12V
-0.36%/K
-0.46%/K
0.05%/K
48°C±2°C
12A
1000V



Warranty

25-year limited warranty of 80% power output;

12-year limited warranty of 90% power output;

5-year limited warranty of materials and worksmanship

Certifications

IEC61215, TUV certification

UL 1703 certification

ETL Class I , Division 2, Groups C and D certification

Mechanical	
Characteristics	
Construction	Tempered glass, silicon cell, EVA, Polyester with Tedlar
Solar Cells	36 cells (156mm x 104mm) in a 4x9 matrix connected in series
Front Cover	High transmission 3.2mm(1/8") glass
Encapsulant	EVA(Double layers)
Back Cover	White polyester
Frame	Anodized aluminum
Junction Box	IP65, UL94-5VA material
Diodes	Schottky by-pass diodes
Terminal	Accept 8-14 AWG wire
Dimensions	39.9in(1014mm)x26.3in(669mm)x1.38in(35mm)
Weight	19.8lb (9.0kg)
Operating Temperature	-40°C ~90°C
Storage Humidity	<90%

