## SOLARSHEAT 1500G





PART NO.	SH1500-G
ENERGY RATING/DAY	6 MJ (SRCC Rating: mildly cloudy
	day, category C)
BTU/DAY	6 kBtu
DIMENSIONS	87"X 43.15" X 3.8"
	221 cm × 109.6 cm × 9.7 cm
GROSS AREA	26 ft² or 2.4 m²
WEIGHT	94 lbs / 42.6 kg
COLOUR	Black
ТУРЕ	Modular solar air collector
MATERIAL	Aluminum extrusion
ABSORBER	Corrugated aluminum -
	perforated or non-perforated
GLAZED	Yes, tempered glass
THERMAL	Polyisocyanurate
INSULATION	
POWER	PV system, 14.5 watts
FLOW RATE	71 CFM
	(backdraft damper installed)
CONTROL	Digital thermostat
FAN	DC
CO <sub>2</sub> REDUCTION	.35 tonne per year
TEMP	120°F (49°C)
MOUNTING	Wall or roof (additional
	flashing and mount required)
MANUFACTURED IN	Canada
WARRANTY	5 yrs. on collector
	1 yr. on electronics
MANUFACTURER	Your Solar Home Inc.


**YOUR SOLAR HOME INC.** is a renewable energy solutions company which manufacturers and develops solar air collection heating systems for residential and industrial use.







Our products are economical, environmentally friendly and can be used for air heating in a variety of different climates and applications.









# SOLARSHEAT **1500G**

#### How it works?

The SolarSheat 1500G is a glazed recirculation solar air collector designed for space heating applications. The 1500G is a supplemental room heating system. A 1500GS (secondary) collector can be attached for larger room heating needs (see the 1500G 2 Pak). The addition of the 1500GS will allow for higher temperatures and better performance in colder climates and hazy conditions.

The SolarSheat 1500G can heat an area of the home or room up to 750 ft<sup>2</sup> or 70 m<sup>2</sup> when the sun is shining. Air is drawn from inside the room through the bottom of the collector and blown out through a duct in the top. The desired temperature is set at the external digital thermostat.

#### Installation

Installation is quick and easy using our patent pending mounting strip, the SolarSheat Mount. Perfect for do-it-yourself or contractor friendly.

#### **External Control**

The SolarSheat 1500G includes an external digital control that allow you to preset your room temperature. The unit can deliver up to 120°F (49°C) estimated for room heating.

#### Fan

The fan allows a proper flow of air up to 90 CFM (without backdraft damper installed) for adequate room heating.



### yoursolarhome.com

299 APPLEWOOD CRESCENT, UNIT 4 VAUGHAN, ONTARIO L4K 4E7 CANADA

SALES: 905.669.2212

1.866.556.5504

FAX: 905.669.2204

E-MAIL: info@yoursolarhome.com

YOUR SOLARSHEAT DEALER: