



Description / Application:

Fully modulating gas fired tankless on demand water heater with power vented flue. Rated for indoor/outdoor use to supply hot water to; domestic hot water systems (direct or indirect using water storage tank applications) with or without recirculation system piping, hydronic heating systems, radiant floor heating, and combined domestic water and heating water systems.

Fuel: NG or LP

Safety Features

- Built in Freeze Protection
- Manual Reset Hi Limit (set at 190°F)
- Overheat Cut Off Fuse
- Inlet/Outlet Thermistors for Constant Temperature Monitoring
- Flue Backdraft Pressure Switch
- GFI Power Supply Connection
- Flame Sensor

Venting and Combustion

- 4" Category III Stainless Steel
- Vertical or Horizontal Installation
- 35' Max Length (90° elbows = 5' equivalent length)
- Power Vent
- Electronic Ignition
- 52 db Fan Noise Level at Max Speed

Accessories:

- TK - BK01 Wall-Mounted Brackets
- TK - TV01 Wall Ventilation Terminator (indoor)
- TK - TV03 Vent Damper
- TK - TV04 Outdoor Vent Cap
- TK - RE02 Temperature Remote Control (optional)


Remote Controller

- 150' Max Distance From Heater
- Non Polarized 18 Gauge Control Wiring


Temp Settings

Dip Switch:	113°F	122°F (*Default)	140°F	182°F					
With RE02 Remote:	99°F	100°F	102°F	104°F	106°F	108°F	109°F	111°F	
	113°F	115°F	117°F	122°F	131°F	140°F	158°F	167°F	

Comments:



August 2005. Irvine, CA



August 2005. Irvine, CA




Model T-K1S



TRUESDAIL
LABORATORIES, INC.

NSF-61 standard⁺ SCAQMD 1146.2⁺⁺



August 2005, Irvine, CA

T-K1S:	HT	W	D	WT	Volt	Amp	Flue	Intake	(Hot/Cold/Gas) Connections
	24	16.5	8	45 lbs.	120	0.84	4" O.D.*	None	3/4" NPT
	Input		Input						
	Max BTU		Min BTU	Eff%	Energy Factor	AFUE	Min Press.	Max Press.	
NG	190,000		15,000	85%	.85	80.2	5.5" wc	10.5" wc	
LP	190,000		17,000	87%	.87	80.2	9.5" wc	14.0" wc	
	GPM		DOE GPH		TDH - Ft.	TDH - PSI	Water PSI	Coil Cap.	
	7.2 - 0.75**		251		39.27-1.06	17 - 0.5	150 - 15 PSI***	≈0.5 GPM	
Installation	Top		Front		Back	(Non Pipe Side)		(Pipe Side)	
Clearances	12"		24"		1"	Rt. Side	2"	Lt. Side	Min 6"

* Category III Required

** 0.6 GPM Required for Continuous Fire After Initial Ignition

*** Pressure Only Relief Valve Required (Min 200,000 BTUs. 150 PSI)

Warranty 7 yrs Heat Exchanger, 2 yrs Parts Only (as of August 2005)

Specification

Flash water heater(s) shall be Model TK1S as manufactured by Takagi Industrial Company Inc. The Flash water heater(s) shall be a copper coil integral fin and tube construction with quick release brass or bronze waterways. Heater(s) will be factory assembled and tested. The heater shall be vented with 4" stainless steel Category III vent pipe a distance not to exceed 35' (equivalent) feet terminating vertically or horizontally as prescribed.

The heater(s) shall be controlled by onboard solid state printed circuit board monitoring incoming and outgoing temperatures with factory installed thermistors, sensing and controlling flow rate to set point temperature which control both air and gas mixture inputs to maintain thermal combustion efficiency. Unit also consists of ground fault interrupter, inline fusing, spark ignition and sensor system, aluminized stainless steel burners, vent pressure switch, Hi limit switch, modulating and proportional gas valves, freeze protection sensor and heating blocks and overheat cut-off fuses.

The water heater(s) shall be CSA listed, exceeds the energy efficiency requirements of ASHRAE 90.1b-1992 and listed by SCAQMD rule 1146.2 Low NOx.