

C35

Xantrex C series - charge controller C35 - 12...24V DC - load 35A



Main

Range of product	Xantrex C series
Device short name	C35
Product or component type	Charge controller
Battery voltage	12 V DC 24 V DC

Complementary

Input voltage	≤ 55 V DC - open circuit
Load current	35 A at 25 °C
Peak current	85 A
Enclosure type	Ventilated
Enclosure material	Powder coated steel
Device mounting	Wall mounted vertical
Cable entry	3/4" and 1" knock-outs
Height	203 mm
Width	127 mm
Depth	64 mm
Product weight	1.2 kg

Environment

AWG gauge	10
Ambient air temperature for operation	0...40 °C
Operating altitude	4572 m
Standards	UL 1741 CSA 22.2 No 107.1-95
Marking	CE

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.