

Thermal Expansion Tanks, In-Line

- Stainless Steel System Connection
- Heavy Duty Butyl Diaphragm
- Polypropylene Tank Liner
- Projection Welded Air Valve



✓ To Submit	Part #	Description	Size	
	MLT5	In-Line Thermal Expansion Tanks, 1 Year Warranty	2 gallon	
	MLST5	In-Line Thermal Expansion Tanks, 5 Year Warranty	2 gallon	
	MLT12	In-Line Thermal Expansion Tanks, 1 Year Warranty	4.4 gallon	
	MLST12	In-Line Thermal Expansion Tanks, 5 Year Warranty	4.4 gallon	

#### WARRANTY

See warranty information for more details.








All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.




# Thermal Expansion Tanks, In-Line

#### In-Line Models

Part #	Tank Vol.		Max. A		λ ght	1	B neter	Sys. Conn.	Ship Wt.	
	Lit.	Gal.	Factor	cm	ins.	cm	ins.	NPTM	kg	lbs.
MLST5	8	2.0	0.45	321	12 <sup>5</sup> ⁄8	203	8	3⁄4	2.3	5
MLST12	17	4.4	0.73	381	15	279	11	3/4	4.0	9





#### In-Line Models

Part #	Tank Vol.		Max. Accept. He		A ight	Dian	3 neter	Sys. Conn.	Ship Wt.	
I alt#	Lit.	Gal.	Factor	cm	ins.	cm	ins.	NPTM	kg	lbs.
MLT5	8	2.0	0.45	321	12 <sup>5</sup> /8	203	8	3⁄4	2.3	5
MLT12	17	4.4	0.73	381	15	279	11	3⁄4	4.0	9

## **Maximum Operating Conditions**

Operating Temperature	200°F (93°C)			
Working Pressure	150 PSIG (10.5 bar)			

### **Specifications**

Description	Standard Construction			
Standard Factory Pre-charge	40 PSIG (2.8 bar)			
System Connection	Stainless Steel			
Diaphragm	Butyl			
Liner Material	Polypropylene			

All dimensions and weights are approximate. Complies with Low Lead Plumbing Law







All dimensions listed are nominal. MAINLINE® reserves the right to make product and material changes at any time without notice.