



TRUESDAIL
LABORATORIES, INC.

NSF-61 Standard+ SCAQMD 1146.2**



Description / Application:

Fully modulating gas fired tankless on demand water heater with sealed combustion (optional) and power vented flue. Rated for indoor/outdoor use to supply hot water to: domestic hot water systems (direct and indirect using water storage tank applications) with or without recirculation system piping, hydronic heating systems, radiant floor heating, and combined domestic water and heating water systems.

Fuel: NG or LP

Safety Features

- Built in Freeze Protection
- Manual Reset Hi Limit (Set at 194°F)
- Overheat Cut Off Fuse
- Inlet/Outlet Thermistors for Constant Temperature Monitoring
- Air-Fuel Ratio Rod
- GFI Power Supply Connection
- Flame Sensor

Venting and Combustion


- 4" Category III Stainless Steel
- Vertical or Horizontal Installation
- 50' Max Length, 5 elbows max (90° elbows = 5' equivalent length)
- Power Vent
- Electronic Ignition
- 3" Combustion Air Intake (with optional kit)

Accessories:


- TK - TV03 Vent Damper
- TK - TV05 Wall Ventilation Terminator (Direct Vent)
- TK - TV01 Wall Ventilation Terminator (indoor)
- TK - TV04 Outdoor Vent Cap
- TK - TV10 Direct Vent Conversion Kit (optional)
- TM - RE10 Temperature Remote Control (optional)

Remote Controller

- 400' Max Distance From Heater
- Non Polarized 18 Gauge Control Wiring



*Above shown rate is based on single unit only.



Temp Settings

Dip Switch:	104°F	113°F	122°F (default)	131°F	140°F	158°F	176°F	185°F	
With RE10 Remote:	99°F	100°F	102°F	104°F	106°F	108°F	110°F	111°F	113°F
	113°F	115°F	117°F	122°F	131°F	140°F	158°F	167°F	182°F
	158°F	185°F							

Takagi Industrial CO. USA, Inc.
 5 Whatney Irvine, CA 92618
 888.882.5244 www.takagi.com

+Complied w/NSF-61 standard (certified by TL Lab)
 ++Met SCAQMD rule 1146.2 (certified by BR Lab)