


**6-Year Limited Tank/6-Year Limited Parts Warranty\***

All Solar Storage Tanks have a Fused Ceramic Shield applied under pressure and fired at 1600°F to completely cover the tank interior. This provides a tough interior surface for storage tanks and maximum protection against the wearing effects of high-volume and high-temperature water.

- **2" Non-CFC Foam Insulation**  
Foam insulation traps heat within the tank, saving energy.
- **Anode Rod**  
Promotes longer tank life through protection against corrosion of tank interior.
- **Factory-Supplied Top Temperature and Pressure Relief Valve**
- **Factory-Installed Dielectric Nipples**
- **Pre-Wired Sensor Lead**  
From storage sensor mounting stud to top of tank.  
Does not include sensor.
- **Water Connections**  
Accessible from four 3/4" dielectric nipples located on top of tank.
- **4500-Watt Heating Element and Automatic Thermostat**  
Where a back-up system is desired.
- **UL Listed**



\*For complete warranty information consult the written warranty of American Water Heaters found at [www.americanwaterheater.com](http://www.americanwaterheater.com), or call (800) 456-9805.



MODEL NUMBER	GALLON CAPACITY	HEIGHT WATER CONN.	JACKET DIAMETER A	HEIGHT TOP OF TANK B	HEIGHT TOP T&P C	APPROX. SHIP WEIGHT
SE62-80H-0455	80	60-1/4	24	59-1/4	59-1/4	191
SE62-119R-0455	119	62	28	61-1/2	61-1/2	278

\*Limited warranty on tank and parts. Complete details in manual.

## Specification

Furnish and install, where indicated, in accordance with manufacturer's instructions and in compliance with all rules and regulations of authorities having jurisdiction.

Storage tank(s) shall be American® Model \_\_\_\_\_ as manufactured by American Water Heaters or equivalent. Storage tank(s) shall have a nominal storage capacity of \_\_\_\_\_ gallons, recovery of \_\_\_\_\_ GPH at \_\_\_\_\_ ° F temperature rise and supplied with auxiliary heating elements rated at 4.5 KW, \_\_\_\_\_ volt. Storage tank(s) are hydrostatic tested at 300 PSI having a working pressure of 150 PSI and shall have a Fused Ceramic Shield internally lined tank applied under pressure and fired at 1600° F allowing for maximum protection. Storage tank(s) shall be equipped with an approved pressure and temperature relief valve. The outer jacketing shall have a baked enamel finish. The tank shall be foam insulated with an EPA-approved, non-CFC material 2" in thickness. Storage tank(s) shall have a 6-year limited warranty against corrosion as outlined in the written warranty.

## Distributed By:

### Order Entry and Sales

500 Princeton Road (FEDEX, UPS)  
Johnson City, TN 37601-2030  
P.O. Box 4808 (Mailing)  
Johnson City, TN 37602-4808  
(800) 937-1037  
FAX (800) 581-7224

### Warranty and Service

500 Princeton Road (FEDEX, UPS)  
Johnson City, TN 37601-2030  
P.O. Box 1597 (Mailing)  
Johnson City, TN 37605-1597  
(800) 456-9805  
FAX (800) 999-5210